

CONTEMPORARY VISIONS, LLC DBA SONNEMAN - A WAY OF LIGHT TEST REPORT

SCOPE OF WORK

LED Performance Testing

MODEL NUMBER

25FN4RBVSTSK2700NSCF5KV1 (500mA)

PROJECT NUMBER

G104629313

REPORT NUMBER

104629313CRT-082

ISSUE DATE

4/30/2021

REVISED DATE

None

TEST DATES

4/29/2021

DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-3407

© 2017 INTERTEK



REPORT NUMBER

104629313CRT-082

MODEL NUMBER(s)

25FN4RBVSTSK2700NSCFSKV1 (500MA)

REPORT RENDERED TO:

CONTEMPORARY VISIONS, LLC DBA SONNEMAN - A WAY OF LIGHT
20 NORTH AVE
LARCHMONT, NY 10538-2463
USA

STATEMENT OF LIMITATION

NVLAP Lab Code 100402-0. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

AUTHORIZATION

The testing performed was authorized by signed quote number Qu-01145763-1.

TEST STANDARDS

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

In Charge of Testing:



Kristie Ray
Team Lead, Engineering
Lighting Division

Reviewer:



Jeff Davis
Lighting Performance Technical Lead
Lighting Division

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

SAMPLE INFORMATION

REPORT NO. 104629313CRT-082

Aperture	Power	Finish	Nominal CCT	Regress
4"	500mA	Satin Black	2700K	Standard

ITEMS RECEIVED

Item No.	Control No.	Model No.	Description	Shape/ Style	Type	Received
1	CRT2103221293-002-036	25L42700V1	Light Engine	N/A	Production	3/22/2021
2	CRT2103221293-002-048	PHB30W-0500-42 @ 500mA	Driver	N/A	Production	3/22/2021
3	CRT2104011108-001-001	25O4NS	Primary Optic	Narrow Spot	Production	4/1/2021
4	CRT2103221293-002-034	25T4RBVSTSK	Trim	Round Bevel	Production	3/22/2021
5	CRT2103221293-002-054	25F4RCFSK	Ring	N/A	Production	3/22/2021
6	CRT2103221293-002-023	25R4R	Reject Plate	N/A	Production	3/22/2021
7	CRT2103231335-003	25HICCP	Housing	N/A	Production	3/23/2021

TESTED SAMPLE CONFIGURATIONS

Config No.	Tested Model No.	Item Nos. Utilized
1	25FN4RBVSTSK2700NSCFKSV1 (500mA)	1-7

SAMPLE PHOTOS - TESTED CONFIGURATIONS



SUMMARY

REPORT NO. 104629313CRT-082

PRODUCT INFORMATION AND SUMMARY OF DATA

Product Model No.:	25FN4RBVSTSK2700NSCF5KV1 (500mA)
Product Description:	Recessed Downlight
LED Model No.:	Cree CXB1820
Driver Model No.:	ERP PHB30W-0500-42
Light Source:	LED

Criteria	Results
Light Output (lumens)	1672.2
Input Power (W) @ 120 (Vac)	20.42
Lumen Efficacy (lm/W)	81.87
Input Power Factor () @ 120 (Vac)	0.990

TEST METHODS

SEASONING IN SAMPLE ORIENTATION - LED PRODUCTS

No seasoning was performed in accordance with IESNA LM-79.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

A Type C Mirror Goniophotometer system was used to measure the luminous intensity (candela) at each angle of distribution for the EUT. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position near the EUT at equal height and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

REPORT NO. 104629313CRT-082

Test Configuration	Tested Model No.	Pass/Fail/NA
1	25FN4RBVSTSK2700NSCF5KV1 (500mA)	NA

PHOTOMETRIC AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation	Input Voltage (Vac)	Input Current (mA)	Input Power (W)	Input Power Factor (I)
Up	120.04	171.8	20.42	0.990

Light Output (lm)	Lumen Efficacy (lm/W)
1672.2	81.9

INTENSITY SUMMARY - CANDELA

Angle	0	22.5	45	67.5	90
0	10793	10793	10793	10793	10793
5	8882	8997	9050	9082	9080
10	5001	5032	5016	5005	5000
15	2174	2131	2100	2089	2089
20	849	825	808	809	826
25	363	352	343	344	353
30	220	212	208	210	213
35	158	151	148	151	154
40	112	106	105	107	110
45	68	67	67	69	70
50	20	19	18	18	18
55	2	2	2	2	2
60	0	0	0	0	0
65	0	0	0	0	0
70	0	0	0	0	0
75	0	0	0	0	0
80	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0
95	0	0	0	0	0
100	0	0	0	0	0
105	0	0	0	0	0
110	0	0	0	0	0
115	0	0	0	0	0
120	0	0	0	0	0
125	0	0	0	0	0
130	0	0	0	0	0
135	0	0	0	0	0
140	0	0	0	0	0
145	0	0	0	0	0
150	0	0	0	0	0
155	0	0	0	0	0
160	0	0	0	0	0
165	0	0	0	0	0
170	0	0	0	0	0
175	0	0	0	0	0
180	0	0	0	0	0

Entire luminous intensity matrix found in .IES file





REPORT NO. 104629313CRT-082

ORIENTATION AND ALIGNMENT OF EUT

Luminous Opening		
Length (ft)	Width (ft)	Height (ft)
0.33	0.33	0.00
0°-180° H	90°-270° H	0°-180° V


Test Distance (ft)
29.6

PHOTOMETRIC CENTER OF EUT



REPORT NO. 104629313CRT-082

ILLUMINANCE SUMMARY



ZONAL LUMENS

Zonal Lumen Summary					
Zone	Lumens	Luminaire	Zone	Lumens	Total
0-30	1,522.9	91.1%	0-10	722.2	43.2%
0-40	1,618.4	96.8%	10-20	619.3	37.0%
0-60	1,672.2	100.0%	20-30	181.4	10.8%
60-90	0.0	0.0%	30-40	95.5	5.7%
70-100	0.0	0.0%	40-50	49.9	3.0%
90-120	0.0	0.0%	50-60	4.0	0.2%
0-90	1,672.2	100.0%	60-70	0.0	0.0%
90-180	0.0	0.0%	70-80	0.0	0.0%
0-180	1,672.2	100.0%	80-90	0.0	0.0%
			90-100	0.0	0.0%
			100-110	0.0	0.0%
			110-120	0.0	0.0%
			120-130	0.0	0.0%
			130-140	0.0	0.0%
			140-150	0.0	0.0%
			150-160	0.0	0.0%
			160-170	0.0	0.0%
			170-180	0.0	0.0%

EQUIPMENT LIST

REPORT NO. 104629313CRT-082

#	Equipment	Model No	Control No.	Last Cal	Cal Due
1	LSI High Speed Mirror Goniophotometer	6440	---	4/15/2021	7/15/2021
2	Elgar AC Power Supply	CW1251	---	VBU	VBU
3	Yokogawa Power Analyzer	WT210	E464	5/11/2020	5/11/2021
4	Traceable Hygrothermometer	4800	L204	2/21/2021	2/21/2022
5	M-D Building Products Digital Level	Smart Tool	307-L112	5/14/2020	5/14/2021
6	Sorenson DC Power Supply	XG 150-10	---	VBU	VBU
7	Traceable Thermometer	4800	L204	2/12/2021	2/12/2022
8	Bosch Distance Laser	Pro GLM 20	L211	3/3/2021	3/3/2022

REVISION HISTORY

#	Revision Date	Updated By	Reviewed By	Description of Change
---	None	---	---	---
---	---	---	---	---
---	---	---	---	---