NOTES

Fixture Type:

Project:

Location:

Model Numbers:

DESCRIPTION

- Intervals Recessed 3″ Downlights offer specification-grade performance and features, in a completely modular and field-configurable system;
- Every light engine integrates with any of the trims, and every trim works with all of the ceiling application and housing options.

DELIVERED LUMENS	Up to 703Lm
WATTS	~13W
OPTICS Field-Changeable	15° / 25° / 32°
TRIM OPTIONS	Round Bevel Square Bevel

COLOR TEMPERATURE

3000K 1800K

Min. 95CRI

AVAILABLE TRIM FINISHES

Satin Black

Satin Aluminium

Satin White

CEILING APPLICATIONS

Flanged

Mud-In

Millwork

LIGHT ENGINE

- Up to 703 delivered lumens, 13W, field-replaceable
- Cold forged aluminum with anodized champagne finish provides a lightweight heat sink with excellent thermal performance in a compact size;
- LTF chip-on-board LED with warm dimming from 3000K to 1800K, min. 95 CRI, and 3-Step color binning.

DRIVER

- Standard driver is field-replaceable and accessible from below the ceiling;
- 120/277VAC input;
- 1% dimming with forward/reverse phase (at 120VAC) and 0-10V dimming controls;
- Multiple drivers with additional dimming protocols available.

OPTICS

- Field-changeable TIR optics with a smooth beam, no softening lens required;
- Available in narrow spot (15º), medium spot (25º), and wide spot (32º) distributions;
- Up to 2 optical accessories can be used without any extra holder, to further refine lighting effects.

TRIMS

- Die cast aluminum construction for strength and durability;
- Up to 40 degrees of continuously adjustable tilt with no center beam clipping, controlled by a drive screw for precise positioning;
- Fully adjustable rotational aiming, with locking screw;
- Patent pending sliding shade eliminates line-of-sight into the ceiling cavity or housing, regardless of tilt angle;
- Trim cover provides a beveled appearance in the desired finish, secured with ball catches for easy removal for aiming adjustment;
- Round adjustable trims feature stainless steel spring wings for tool-free installation into any position and easy twist-out removal for in-field servicing;
- Square adjustable trims feature swing-out screw clamp mounting for precise alignment;
- Suitable for ceiling thicknesses from 0.5″-1.5″;
- Delivered lumens are maintained through the full range of ceiling thicknesses;
- Available in powder coated satin white and satin black, and painted satin aluminum finishes.

CEILING APPLICATIONS

- Available in flanged, flangeless mud-in, and flangeless millwork, all in die cast aluminum;
- Flanged ceiling application features a tapered Feather Edge profile for a minimal appearance and provides a universal solution for all ceiling types.
  Available in trim-coordinating finishes of satin black, satin aluminum, and field-paintable satin white;
- Flangeless mud-in ceiling application securely attaches to the housing, providing a flush and seamless appearance in gypsum and plaster ceilings with no warping or cracking.
  Available in field-paintable satin white finish;
- Flangeless millwork ceiling application provides a flangeless appearance in wood or stone ceilings.
  Available in field-paintable satin white finish.

HOUSINGS/INSTALLATION

- Patent pending two-part junction box and driver housing is included for remodel and new construction installations and allows for easy servicing and inspection from below the ceiling;
- Junction box has two ½″ trade size knockouts and is rated for through-wiring of 12AWG conductors;
- New Construction Pan and IC Housing feature a patent pending field-changeable adapter door, allowing the same pan or housing to be converted to a different size (2″, 3″, or 4″) or shape (round or square) in the field, up until the ceiling is installed;
- Square adapter doors feature a reject collar that is adjustable 90 degrees and has gunsight notches for precise alignment;
- New Construction Pan and IC Housing include adjustable hanger bars for installation to wood joists or T-grid suspended ceilings;
- Adjustable height butterfly brackets are available for mounting with the available C-channel, the included adjustable hanger bars, EMT, or furring strip.

RATINGS/CERTIFICATIONS

- ETL listed to US and Canadian standards (UL1598) for damp locations;
- Meets CA Title 24 Part 6 JA8 High Efficacy LED and Chicago plenum requirements when used with standard driver and IC housing;
- 5 year limited warranty (see website for terms);
- Emergency Use: 35W High Efficiency Invertor with integrated battery backup and test switch available.

HOW TO ORDER

Build your item numbers for the rough-in section (includes housing and driver) and the finishing section (includes LED light engine and trim), plus any accessories ordered separately.

MADE-TO-ORDER PROGRAM ORDERING INFORMATION

ROUGH-IN SECTION ITEM NUMBER (Specify from left to right, filling in each box, e.g. 25RN3RICCPSTANFWD00V1)

25RN3					**WD**			**V1**
Family	**Aperture Shape**	**Mounting**	**Driver**	**Driver Location**	**Light Source/Power**	**Butterfly Brackets**	**Flangeless Mud-In**	**Version**
25RN3 Intervals Recessed Rough-In Section	**R** Round **S** Square	**ICCP** New Construction IC Housing, Chicago Plenum **NCPA** New Construction Pan **RMDL** Remodel	**STAN** ERP, 120/277V, Forward Phase, Reverse Phase, and 0-10V Dimming to 1% **PEQ0** Lutron Hi-lume Premier, 120/277V, EcoSystem Dimming to 0.1% with Soft-on and Fade-to-Black **DPOE** (1,2) Power Over Ethernet	**F** Fixture **R*** Remote	**WD** Warm Dimming (13W)	**0** No **1** (3) Yes (Included)	**0** No **1** (3) Yes (Included)	**V1** Version 1

*Only necessary if the driver will be physically remoted from the luminaire.

FINISHING SECTION ITEM NUMBER (Specify from left to right, filling in each box, e.g. 25FN3RADSTSW3018NSCFSWV1HEX)

25FN3		**AD**	**ST**		**3018**				**V1**		
Family	**Aperture Shape**	**Trim Style**	**Regress**	**Trim Finish**	**CCT**	**Optic**	**Ceiling Application**	**Ceiling Application Finish**	**Version**	**Optical Accessories** (blank if none; up to two options)	
25FN3 Intervals Recessed Finishing Section	**R** Round **S** Square	**AD** Adjustable	**ST** Standard	**SW** (4) ○ Satin White **SK** ● Satin Black **SA** (4) ● Satin Aluminum	**3018** 3000K - 1800K	**NS** 15º Narrow Spot **MS** 25º Medium Spot **WS** 32º Wide Spot	**CF** Flanged **MW** Flangeless Millwork **NA** (5,6) Flangeless Mud-In	**SW** (7) ○ Satin White **SK** ● Satin Black **SA** ● Satin Aluminum	**V1** Version 1	**HEX** Honeycomb Louver *(If second accessory is not specified, will include Clear Glass Lens)* **LIN** Linear Spread Lens **SOL** Microprism Lens **CLR** Clear Glass Lens	

(1)Requires Driver Location R
(2) Special order, contact factory; requires enclosure provided by others
(3) Requires Mounting ICCP or NCPA
(4) Includes Satin Black interior
(5) Requires Rough-In Section Mounting ICCP or NCPA. Select Flangeless Mud-in: 1 in the rough-in section table, or order separately from the accessories table.
(6) Requires Ceiling Application Finish SW
(7) Field-paintable

ACCESSORIES ORDERING INFORMATION

ACCESSORIES ITEM NUMBERS (e.g. 25ZCCH27)

25Z		
Family	**Style**	**Size/Finish (if applicable)**
25Z Intervals Recessed Accessories	**BTF** Butterfly Bracket Set (set of 2) **CCH** C-Channel (set of 2, requires butterfly brackets) **LWP** 20′ Luminaire Whip for remote driver **RGP03** 3″ Round Goof Plate **SGP03** 3″ Square Goof Plate **HEX03** 3″ Hex Louver **LIN03** 3″ Linear Spread Lens **SOL03** 3″ Microprism Lens **CLR03** 3″ Clear Glass Lens **IIS35HE** Iota 35W High Efficiency Inverter	**27** 27″ C-Channel Set **52** 52″ C-Channel Set **SW** Satin White Goof Plate **SK** Satin Black Goof Plate **SA** Satin Aluminum Goof Plate

ADDITIONAL OPTICS

OPTICS (e.g. 25O2NS)

25O3	
Family	**Beam Angle**
25O3 Intervals Recessed Optic	**NS** 15º Narrow Spot **MS** 25º Medium Spot **WS** 32º Wide Spot

ADDITIONAL CEILING APPLICATIONS

CEILING APPLICATIONS (e.g. 25F3RFMSW)

25F3			
Family	**Aperture Shape**	**Style**	**Finish**
25F3 Intervals Recessed Ceiling Application	**R** Round **S** Square	**CF** Ceiling Flange **FM** Flangeless Mud-In **MW** Flangeless Millwork	**SW** ○ Satin White **SK** ● Satin Black (Ceiling Flange only) **SA** Satin Aluminum (Ceiling Flange only)

DIMENSIONS

Round Adjustable Trim



Round Ceiling Flange



Round Flangeless Mud-in Plate



Round Flangeless Millwork Collar



Square Adjustable Trim



Square Ceiling Flange



Square Flangeless Mud-in Plate



Square Flangeless Millwork Collar



Driver Housing



New Constuction Pan



IC Housing



IC Housing with 3″ Round Adapter Door





IC Housing with 3″ Square Adapter Door





IC Housing with Adjustable Butterfly Brackets

Front and Back Application



Side Application



Adjustable Butterfly Brackets

Minimum Height



Maximum Height



INDOOR PHOTOMETRIC REPORT

3" RECESSED DOWNLIGHT NARROW SPOT 15°

Description: 3 inch Round Adjustable Trim Warm Dimming Narrow Spot **| Lamp Output:** 1 lamp, rated Lumens/lamp: 629.1
Input Wattage: 13.3464 **Max Cd:** 5,840.3 at horizontal: 135°, Vertical: 2° **| Spacing Criterion:** @ 0 = 0.22/ @ 90 = 0.26 | **High Output**

POLAR CANDELA



ILLUMINANCE AT A DISTANCE

Height (ft)	Center Beam Footcandle	Beam Spread (ft) Horizontal	Beam Spread (ft) Vertical	Field Spread (ft) Horizontal	Field Spread (ft) Vertical
8.00	88.14 fc	2.1	2.2	4.6	4.8
10.00	56.41 fc	2.7	2.7	5.7	6.0
12.00	39.18 fc	3.2	3.3	6.9	7.2
14.00	28.78 fc	3.7	3.8	8.0	8.4
16.00	22.04 fc	4.3	4.4	9.1	9.6
		Beam Angle		Field Angle	
		15.2°	15.6°	31.9°	33.3°

CANDELA TABLE - TYPE C

	0	45	90	135	180	225	270	315	360
0	5641	5641	5641	5641	5641	5641	5641	5641	5641
5	3393	3968	4501	5130	5010	4018	3567	3278	3393
15	531	727	920	1202	1125	670	494	450	531
25	75	101	127	168	160	104	81	70	75
35	19	25	29	35	32	24	20	19	19
45	6	7	8	8	7	6	6	5	6
55	2	2	2	2	2	2	2	2	2
65	2	2	2	2	2	2	2	2	2
75	0	0	0	1	0	0	0	0	0
85	0	0	0	0	0	0	0	0	0
90	0	0	0	0	0	0	0	0	0

3" RECESSED DOWNLIGHT MEDIUM SPOT 25°

Description: 3 inch Round Adjustable Trim Warm Dimming Medium Spot **| Lamp Output:** 1 lamp, rated Lumens/lamp: 597.1
Input Wattage: 13.317 **Max Cd:** 2,563.7 at horizontal: 135°, Vertical: 2° **| Spacing Criterion:** @ 0 = 0.37/ @ 90 = 0.42 | **High Output**

POLAR CANDELA



ILLUMINANCE AT A DISTANCE

Height (ft)	Center Beam Footcandle	Beam Spread (ft) Horizontal	Beam Spread (ft) Vertical	Field Spread (ft) Horizontal	Field Spread (ft) Vertical
8.00	39.45 fc	3.5	3.6	6.9	7.0
10.00	25.25 fc	4.4	4.5	8.6	8.8
12.00	17.53 fc	5.3	5.4	10.3	10.5
14.00	12.88 fc	6.1	6.3	12.0	12.3
16.00	9.86 fc	7.0	7.2	13.7	14.0
		Beam Angle		Field Angle	
		24.7°	25.5°	46.5°	47.3°

CANDELA TABLE - TYPE C

	0	45	90	135	180	225	270	315	360
0	2525	2525	2525	2525	2525	2525	2525	2525	2525
5	2144	2321	2447	2487	2431	2245	2115	2075	2144
15	714	922	1152	1314	1206	847	669	645	714
25	151	204	262	308	271	172	135	130	151
35	34	44	55	61	52	35	30	30	34
45	8	11	14	14	10	7	7	7	8
55	3	3	2	2	2	2	2	2	3
65	2	2	2	2	2	2	2	2	2
75	0	0	1	1	0	0	0	0	0
85	0	0	0	0	0	0	0	0	0
90	0	0	0	0	0	0	0	0	0

3" RECESSED DOWNLIGHT WIDE SPOT 32°

Description: 3 inch Round Adjustable Trim Warm Dimming Wide Spot **| Lamp Output:** 1 lamp, rated Lumens/lamp: 703
Input Wattage: 13.3184 **Max Cd:** 2,304.7 at horizontal: 90°, Vertical: 6° **| Spacing Criterion:** @ 0 = 0.53/ @ 90 = 0.55 | **High Output**

POLAR CANDELA



ILLUMINANCE AT A DISTANCE

Height (ft)	Center Beam Footcandle	Beam Spread (ft) Horizontal	Beam Spread (ft) Vertical	Field Spread (ft) Horizontal	Field Spread (ft) Vertical
8.00	33.95 fc	4.6	4.6	7.6	7.7
10.00	21.73 fc	5.7	5.8	9.4	9.7
12.00	15.09 fc	6.8	6.9	11.3	11.6
14.00	11.08 fc	8.0	8.1	13.2	13.5
16.00	8.49 fc	9.1	9.2	15.1	15.5
		Beam Angle		Field Angle	
		31.8°	32.2°	50.5°	51.6°

CANDELA TABLE - TYPE C

	0	45	90	135	180	225	270	315	360
0	2172	2172	2172	2172	2172	2172	2172	2172	2172
5	2085	2242	2298	2237	2083	1896	1836	1917	2085
15	1178	1686	1922	1730	1221	775	650	795	1178
25	221	500	662	513	242	99	77	101	221
35	25	47	66	47	26	17	15	17	25
45	5	12	15	13	7	3	3	3	5
55	2	2	3	2	2	2	2	1	2
65	1	1	2	2	1	1	1	1	1
75	0	0	1	1	0	0	0	0	0
85	0	0	0	0	0	0	0	0	0
90	0	0	0	0	0	0	0	0	0